

MV 125 Series



Application

- Decoration of supply and exhaust vents of public, residential and industrial ventilation systems.
- Used for correct air flow distribution in premises.
- Wall or ceiling mounting.

Design

- Made of quality and durable plastic.
- Multi-element structure. The internal part is fixed to the base with latches for easy cleaning without dismantling.
- Fixing with screw or lugs depending on modification.

Colour modifications



Modifications

MV 125 - basic modification



- Screw fixing.
- **MV 125 s** - model with a protecting screen and screw fixing.
- **MV 125 M** - model with fixing lugs.
- **MV 125 Ms** - model with fixing lugs and a protecting insect screen.



MV 125 VD - model with four-element connecting flange (VD)



- Screw fixing.
- Equipped with four-element connecting flange with adjustable diameter for connection to Ø 100-150 mm round air duct.
- **MV 125 VLS** - grille model with screw fixing and a protecting insect screen.
- **MV 125 VDM** - grille model with fixing lugs.
- **MV 125 VDMs** - grille model with fixing lugs and a protecting insect screen.



Overall dimensions

Model	Dimensions, mm							Air pass, m ²	Fig. no.
	H	B	L	L1	H1	B1	D		
MV 125	251	182	16	-	226	157	-	0,0127	1, 2
MV 125 VD	251	182	16	41	226	157	100-150	0,0127	1, 3




Fig. 1




Fig. 2




Fig. 3